



EcoQuip[®]

Vapor Abrasive[®] Blast Equipment



PROVEN QUALITY. LEADING TECHNOLOGY.

EcoQuip Vapor Abrasive Blast Equipment

Maximum blast power, minimal dust

Vapor Abrasive blasting: A cleaner, easier path to profitable results

No longer is it necessary to put up with the high cost of purchasing, cleaning up and disposing of large volumes of media to achieve quality results in record time.

EcoQuip's Vapor Abrasive technology gives you an equally powerful blast that works quickly like dry blasting, but requires a fraction of the media and the time required to clean it up. That leaves you with savings in material, labor and disposal costs, which you can turn into profit.

Less dust than dry blasting, less water than traditional water-based blasting

EcoQuip Vapor Abrasive technology differs significantly from dry, slurry and traditional water-based blast methods. EcoQuip employs its own patent-pending GRX Flow Dynamics technology, which optimizes the air, water and media ratio. The result is a fine mist with a blast that is powerful like the dry method, but with up to 92 percent less airborne dust.

Unlike conventional wet blasting, the mist expelled by EcoQuip quickly evaporates. No pools of water left behind. No toxic runoff to worry about. And because EcoQuip uses significantly less media than wet blasting, clean-up is minimal.*

The result is a cleaner, better-contained process that current customers will appreciate and future customers will prefer.

*Individual results may vary.
If hazardous materials are being blasted, containment or clean-up may be required.*

"The EcoQuip EQ600 was the only solution found that could clean the efflorescence of the stone buildings at Virginia Tech quickly and efficiently without damaging the stone, the mortar and the concrete cast. The versatility of the EQ600 to blast at extremely low pressures, and at the same time allow for a high volume rinse, gave us unbelievable results."

- David J. Funk,
D&D Solutions

"Before we got EcoQuip, we blasted at night to avoid complaints about the dust. Now we can blast during the day, which is much more convenient, and air quality during blasting is much better."

- Frank Wheatley,
Colonna's Shipyard Inc.

"We used an EcoQuip vapor blast unit to blast the interior of a building. The dust was very well-contained and we had a lot less water runoff than with wet abrasive units we have used in the past."

- Anthony Russo,
Brock Services LLC

Three-Year Extended Warranty

Graco stands behind every piece of equipment it manufactures. EcoQuip offers a three-year extended warranty, the longest in the blasting industry. See product manuals for specific warranty details.



Third party testing supports the fact that EcoQuip suppressed up to 92 percent of airborne dust compared to dry blasting on steel.

EcoQuip's Quality of Manufacturing

Built to take a beating

EcoQuip is built by Graco entirely of heavy-duty stainless steel crash frames to withstand the toughest conditions and provide years of solid service. When it is time for servicing, help is easy to find through Graco's worldwide distribution and service network.

Graco is a leading manufacturer of fluid handling equipment. Since 1926, Graco has been a trusted worldwide supplier to industries that rely on high quality, well-engineered machinery, including the protective coatings industry. We understand the challenges faced by today's contractor and create durable tools to help you achieve the highest quality results and the greatest success possible.

3-year warranty*

- Extra-long reliability support
- An industry first

* Please see warranty for complete details

Patented system design

- Lightweight
- Maneuvers easily in space-restricted locations

Galvanized blast pot

- Long-lasting quality and performance

Safety-minded design

- Standalone units stack safely for warehousing
- 5x safety rated frame

Easy-access servicing

- Controls conveniently located together

Heavy duty frame

- Rugged stainless steel frame and components

GRX Flow Dynamics

- Patent-pending technology for an optimal blast mix

Achieves industry standards

- NACE No. 1
- SSPC-SP 5

Auto-venting valve

- Patent-pending auto valve
- Automatically relieves excess air for optimal media flow

Single Selector Switch

- Set up once, change modes easily
- Patent pending



DR

EcoQuip Makes the Job Easy

Compare for yourself

Better than dry blasting

- Consumes far less media
- Eliminates up to 92 percent of airborne dust
- Saves on clean-up and disposal costs
- A quick and powerful alternative to dry blasting
- Adjustable to a wide range of blast pressures
- Works on virtually any surface
- Won't damage substrates*
- Works with all job-appropriate media
- Effective in rain and high humidity

Better than slurry and traditional water-based blasting

- Uses far less media
- Uses far less water
- No toxic wastewater runoff**
- No large slurry mess to clean up
- Adjustable to a wide range of blast pressures
- Effective in virtually any application environment

Handles most every application type

- Graffiti cleanup
- Paint layer removal
- Marine coating removal
- Rust and corrosion removal
- Industrial coating and lining removal
- General metal, stone and wood cleaning
- Lead and asbestos abatement
- Building and site maintenance
- Monument and artifact restoration
- Roadway marking removal
- Architectural stripping and cleaning

EcoQuip advantages

- Far less media results in material savings
- Blast pressure options from 30 to 125 psi (2.1 to 8.7 bar)
- Extensive worldwide distribution and service network
- Cleans without damaging mortar or sub-surfaces
- Profiles surfaces for the best coating adhesion
- Effective on both hard and fragile surfaces
- Less impact on surrounding environment**
- Reduced containment measures needed**
- Less restrictive PPE requirements**
- Easy, one-step cleaning process

**When blasting with recommended media at appropriate pressure*

***Assumes blasting without hazardous media or target surface. If hazardous materials are involved, more PPE may be needed and containment or clean-up may be required.*

EcoQuip Technology Leads the Way

Vapor Abrasive blast systems for coating removal and surface prep



Three-year Extended Warranty

Graco stands behind every piece of equipment it manufactures. EcoQuip offers a three-year extended warranty, the longest in the blasting industry. See product manuals for specific warranty details.

EQ100m

Compact, fully portable entry level unit

With its built-in hand truck, slide rails and convenient lifting eye, the patented EQ100m design facilitates easy portability. It fits in the bed of most standard pickup trucks. The EQ100m can accommodate any abrasive heavier than water and, when coupled with an air compressor that can produce 165-375 cfm @ 100+ psi, the EQ100m blasts from 30-125 psi (2-8.6 bar). It's a tough worker, capable of handling any type of project, from cleaning to surface preparation.



Model/Part No.	EQ100m
Unit Dimensions (W x H x D)	34 x 25 x 46.5 in (86 x 64 x 118 cm)
Weight	360 lb (163.3kg) dry / 550 lb (249.5 kg) wet
Air Capacity	165-375 cfm (4.7 – 10.6 m³/min)
Pot Media Capacity	250 lb (113.4 kg)
Blast Pressure	30-125 psi (2-8.6 bar/0.21-0.86 MPa)
Water Tank Capacity	10 gal (38 L)
Blast Hose	1 in ID (25 mm) x 50 ft (15 m) 2-ply
Nozzle Size (included)	#7
Available Accessories	Hose extensions, extension wands and nozzles
Warranty*	Complete machine for three years from original purchase date, less wearable parts

For the best production, use performance media with a medium to fine mesh size.

**Please see complete warranty for details. Specifications subject to change without notice. Standard manufacturer's warranty applies to blast hoses and nozzles.*



EQ300s

Portable, mid to high production unit

The EQ300s is a standalone unit designed to tackle most typical blasting projects. It works with a standard compressor (185-375 cfm) and fits inside a six-foot truck bed. The EQ300s is built according to tough standards, with user-friendly convenience and safety features. It's also sized to stack safely in a warehouse.

EQ600s

Portable, high production unit

Built to withstand the toughest working conditions, the EQ600s is a high-production standalone unit to tackle your largest, most demanding projects. It requires an air compressor at 375-600 cfm and features the same user-friendly features as its smaller version, the EQ300s. It fits inside a six-foot truck bed for easy transport to the jobsite and also stacks easily to conserve warehouse space.



Model/Part No.	EQ300s	EQ600s
Unit Dimensions (W x H x D)	55.75 x 45.5 x 55.5 in (1.42 x 1.15 x 1.41 m)	55.75 x 45.5 x 55.5 in (1.42 x 1.15 x 1.41 m)
Weight	1,050 lb (476.3 kg) dry/2,750 lb (1247 kg) wet	1,100 lb (499 kg) dry/2,800 lb (1270 kg) wet
Air Capacity	185-375 cfm (5.2 – 10.6 m³/min)	375-600 cfm (10.6 – 17 m³/min)
Pot Media Capacity	500 lb (226.8 kg)	500 lb (226.8 kg)
Blast Pressure	30-125 psi (2-8.6 bar/0.21-0.86 MPa)	30-125 psi (2-8.6 bar/0.21-0.86 MPa)
Water Tank Capacity	115 gal (435.3 L)	115 gal (435.3 L)
Blast Hose	1 in ID (25 mm) x 50 ft (15 m) 2-ply	1.25 in ID (25 mm) x 50 ft (15 m) 2-ply
Nozzle Size (included)	#7	#8 Performance
Available Accessories	Hose extensions, extension wands and nozzles	Hose extensions, extension wands and nozzles
Warranty*	Complete machine for three years from original purchase date, less wearable parts	Complete machine for three years from original purchase date, less wearable parts

For the best production, use performance media with a medium to fine mesh size.

**Please see complete warranty for details. Specifications subject to change without notice. Standard manufacturer's warranty applies to blast hoses and nozzles.*

EcoQuip Technology on the Road

Vapor Abrasive blast systems for coating removal and surface prep



EQ200t and EQ400t

Mobile, self-contained units

The mid to high production EQ200t and high production EQ400t are self-contained and always ready to go. The EQ200t is great whether you're working light restoration or removing stubborn industrial coatings. The EQ400t is ready to handle the toughest of applications. Both are designed to be as compact as possible for maneuverability on the jobsite. They are built with safety-inspired features and quality components for maximum, long-lasting reliability. Both are fully self-contained with their own trailers, engines and compressors.

Units shown with Kaeser compressors

Model/ Part No.	EQ200t		EQ400t	
			Tier 3	Tier 4i
Dim. (W x H x D)	174 x 68 x 62 in (4.4 x 1.7 x 1.6 m)		198 x 87 x 76.5 in (5 x 2.2 x 1.9 m)	198 x 87 x 87 in (5 x 2.2 x 2.2 m)
Weight	4000 lb (1814.4 kg) dry / 5750 lb (2608 kg) wet		6000 lb dry (2721 kg) / 8000 lb (3629 kg) wet	7400 lb (3357 kg) dry / 9400 lb (4264 kg) wet
Blast Pressure	30-100 psi (2-6.9 bar/0.21-0.69 MPa)		30-110 psi (2-7.6 bar/0.21-0.76 MPa)	30-125 psi (2-8.7 bar/0.21-0.87 MPa)
Pot Diameter	24 in (61 cm)		24 in (61 cm)	24 in (61 cm)
Pot Media Capacity	500 lb (226.8 kg)		500 lb (226.8 kg)	500 lb (226.8 kg)
Water Tank Cap.	95 gal (359.6 L)		125 gal (473.18 L)	125 gal (473.18 L)
Blast Hose	1 in ID (25 mm) x 50 ft (15 m) 2-ply		1.25 in ID (31.3 mm) x 50 ft (15 m) 2-ply	1.25 in ID (31.3 mm) x 50 ft (15 m) 2-ply
Nozzle Size	#7		#8 Performace	#8 Performace
Accessories	Hose extensions, extension wands and nozzles		Hose extensions, extension wands and nozzles	Hose extensions, extension wands and nozzles
Warranty*	Complete machine for three years from original purchase date, less wearable parts			
ENGINE				
Type	Diesel		Diesel	Diesel
Model	4-cylinder turbo diesel		4-cylinder turbo diesel, tier 3	4-cylinder turbo diesel, tier 4i
Power	45 hp (33.6 kW) @ 2400 rpm		90 hp (67.0 kW) @ 2600 rpm	140 hp (104.4 kW) @ 2200 rpm
Oil System	Pressurized with spin-on filter		Pressurized with spin-on filter	Pressurized with spin-on filter
Battery	12 volt		12 volt	24 volt
Fuel Tank Capacity	8+ hours of operation		8+ hours of operation	8 hours
COMPRESSOR				
Type**	Kaeser single-stage, oil cooled, screw-type		Kaeser single-stage, oil cooled, screw-type	Doosan single-stage, oil cooled, screw-type
Rated Delivery	210 cfm (6 m ³ /min) @ 100 psi (6.9 bar)		375 cfm (10.6 m ³ /min) @ 100 psi (6.9 bar)	425 cfm (12 m ³ /min) @ 100 psi (6.9 bar, 0.69 MPa) 375 cfm (10.6 m ³ /min) @ 150 psi (10.3 bar, 1.0 MPa)
Operating Pressure	100 psi (6.9 bar / 0.69 MPa)		110 psi (7.6 bar / 0.76 MPa)	100-150 psi (6.9-10.3 bar / 0.69-1.03 MPa)
Lubrication System	Pressurized lubrication, spin-on cartr. filter, thermostatically controlled oil-to-air cooler		Pressurized lubrication, spin-on cartr. filter, thermostatically controlled oil-to-air cooler	Pressurized lubrication, spin-on cartr. filter, thermostatically controlled oil-to-air cooler
Pressure Relief	125 psi (8.7 bar/0.87 MPa)		125 psi (8.7 bar/0.87 MPa)	175 (1.2 bar / 12.07 MPa)

For the best production, use performance media with a medium to fine mesh size.

*Please see complete warranty for details. Specifications subject to change without notice. Standard manufacturer's warranty applies to blast hoses, nozzles, engines, compressors and trailer components. **Brands subject to change.

EcoQuip Ordering Information

Vapor abrasive blast systems and accessories

Mobile/Skid Units

- 55177 100 series, mobile unit, complete package, pneumatic or electric deadman
- 55146 300 series, complete package, pneumatic or electric deadman
- 55020 600 series, complete package, pneumatic or electric deadman

Trailer Units with compressor (Tier 3 and Tier 4i compliant)

- 55151 200 series, hydraulic brakes, pneumatic or electric deadman, Tier 3
- 55153 200 series, electric brakes, pneumatic or electric deadman, Tier 3
- 55154 400 series, electric brakes, pneumatic or electric deadman, Tier 3
- 55156 400 series, electric brakes, pneumatic or electric deadman, Tier 4i

100/200/300 complete packages include 1 in. ID, 2-ply hose and #7 standard nozzle. 400/600 complete packages include 1.25 in. ID, 2-ply hose and #8 high performance nozzle.

Hoses

- 55237 Blast Hose, extension, 50 ft (15 m), pneumatic, 1.0 in ID
- 55235 Blast Hose, extension, 50 ft (15 m), electric, 1.0 in ID
- 55077 Blast Hose, extension, 100 ft (30 m), pneumatic, 1.25 in ID
- 55084 Blast Hose, extension, 100 ft (30 m), electric, 1.25 in ID
- 55082 Blast Hose, extension, 50 ft (15 m), electric, 1.25 in ID
- 55073 Blast Hose, extension, 50 ft (15 m), pneumatic, 1.25 in ID
- 55236 Blast Hose, replacement, 50 ft (15 m), pneumatic, 1.0 in ID
- 55234 Blast Hose, replacement, 50 ft (15 m), electric, 1.0 in ID
- 55071 Blast Hose, replacement, 50 ft (15 m), pneumatic, 1.25 in ID
- 55080 Blast Hose, replacement, 50 ft (15 m), electric, 1.25 in ID
- 11284 Safety cable, whip hose - check
- 11365 Coupler safety clip
- 11821 Blast hose coupler gasket fits 1 in and 1.25 in hoses
- 11812 Gasket, cam/groove, 1.50 ID, abrasive media line

Nozzles

- 11710 Standard #7, (EQ100, EQ200, EQ300)
- 11711 Standard #8, (EQ400, EQ600)
- 1307073 High performance #7, (EQ100, EQ300)
- 1307074 High performance #8, (EQ400, EQ600)
- 11308 Replacement trigger, pneumatic deadman, G2
- 55194 Replacement handle, electric deadman
- 55165 1 in ID nozzle extension, 18 in (46 cm), only used on EQ100, EQ200, EQ300 units
- 55166 1 in ID nozzle extension, 24 in (61 cm), only used on EQ100, EQ200, EQ300 units

Pump Cabinets

- 11319 Diaphragm valve repair kit - EQ100, EQ200, EQ300
- 11808 Diaphragm valve repair kit - EQ400, EQ600
- 1307081 Externally piloted air regulator repair kit - EQ100
- 1307081 Externally piloted air regulator repair kit - EQ200, EQ300
- 11965 Externally piloted air regulator repair kit - EQ400, EQ600
- 55225 Air regulator, pump, pot
- 206994 Throat seal liquid, pump





ABOUT GRACO

PROVEN QUALITY. LEADING TECHNOLOGY.

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

GRACO LOCATIONS

MAILING ADDRESS

P.O. Box 1441
Minneapolis, MN 55440-1441
Tel: 612-623-6000
Fax: 612-623-6777

AMERICAS

MINNESOTA

Worldwide Headquarters
Graco Inc.
88-11th Avenue N.E.
Minneapolis, MN 55413

EUROPE

BELGIUM

European Headquarters
Graco N.V.
Industrieterrein-Oude Bunders
Slakweidestraat 31
3630 Maasmechelen,
Belgium
Tel: 32 89 770 700
Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA

Graco Australia Pty Ltd.
Suite 17, 2 Enterprise Drive
Bundoora, Victoria 3083
Australia
Tel: 61 3 9468 8500
Fax: 61 3 9468 8599

CHINA

Graco Hong Kong Ltd.
Shanghai Representative Office
Building 7
1029 Zhongshan Road South
Huangpu District
Shanghai 200011
The People's Republic of China
Tel: 86 21 649 50088
Fax: 86 21 649 50077

INDIA

Graco Hong Kong Ltd.
India Liaison Office
Room 443, Augusta Point
Regus Business Centre 53
Golf Course Road
Gurgaon, Haryana
India 122001
Tel: 91 124 435 4208
Fax: 91 124 435 4001

JAPAN

Graco K.K.
1-27-12 Hayabuchi
Tsuzuki-ku
Yokohama City, Japan 2240025
Tel: 81 45 593 7300
Fax: 81 45 593 7301

KOREA

Graco Korea Inc.
Shinhan Bank Building
4th Floor #1599
Gwanyang-Dong, Dongan-Ku,
Anyang-si, Korea 431-060
Tel: 82 31 476 9400
Fax: 82 31 476 9801

SALES/ DISTRIBUTION/ SERVICE

Call today for product information or to request a demonstration.

877-ECOQUIP (877-326-7847) or visit us at www.ecoquip.com.

Graco Inc. is registered to I.S. EN ISO 9001

North America
Customer Service
800-328-0211
Fax 877-340-6427